

## **RUGGED HANDHELD RP 550**



The PDA offer the intuitive operating system Windows 10 guaranteeing to the user an extraordinary experience and an interconnection at 4.0







Intel Quad-Core
Display 5.5" Full HD
WiFi, Bluetooth, 4G LTE
1D/2D Barcode scanner
Docking station
Windows 10 OS

www.ruggtek.com



Operating System Computing Platform Internation System Memory Storage         At Cores, up to 1,92 GHz           Storage Graphic Intel HD Graphics Intel	Model	RP 550	
Computing Platform System Memory Storage Graphic Display Storage Resolution Touchscreen Bluetooth Bluetooth Bluetooth 4.2 wireless technology Wireless LEE 802.11a/b/g/n/ac compatible Calcular network Location Addio Mono Speaker Addio Mono Speaker Addio Mono Speaker Keyboard Interfaces  LISE 802.11a/b/g Memory Addio Mono Speaker Audio Mono Speaker Seguator Worth Storage Audio Mono Speaker Seguator SiM Card Slot Charging - DC In power Docking connector Built-in BFT and Storage Built-in BFT and Storage Seguator Worth Storage Built-in BFT and Storage SiM Card Slot Charging - DC In power Docking connector Built-in BFT and Storage Built-in BFT and Storage Seguator Cooling System Dimensions Weight Environment **  Cooling System Dimensions Weight Environment **  Cooling System Dimensions Weight Environment **  AC/DC Power Adapter Fanless design - No fan. No noise. Height 180mm, Width 87mm, Depth 21.5mm approx.360g Environment **  Regulatory Ordering Code Adapter for digarette lighter sock, Ac/DC Power Adapter. Fanless Bardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for digarette lighter sock, Ac/DC Power Adapter. Adapter Graphic Storage Adapter Carrying Case, Adapter Car	Operating System	Microsoft Windows 10 Professional	Windows IOT Enterprise LTSC *
System Memory Storage Graphic Intel HD Graphics Display S.5 inch IDSPlay Portrait or Landscape, automatic screen rotation Multi-touch by finger and pen Bluetooth Bluetooth 4.2 wireless technology Class 2 IEEE 802.11a/b/g/n/ac compatible Location Built-in GNSS Support GPS, Glonass and Assisted GPS Built-in GNSS Support GPS, Glonass and Assisted GPS Audio Audi		Intel Atom x5-Z8350	4 Cores, up to 1.92GHz
Intel HD Graphics   15.5 inch   19.5 technology, 500nits   5.5 inch   19.5 technology, 500nits   5.5 inch   19.80 x 1920   Full HD resolution display, 16:9   Portrait or Landscape, automatic screen rotation   Multi-touch by finger and pen   Eluetooth   Bluetooth 4.2 wireless technology   Class 2   LEE 802.11a/b/g/n/ac compatible   2.4GHz and 5.0GHz, Dual Band support   2.4GHz, Dual Band sup	System Memory	4GB	
Intel HD Graphics   15.5 inch   19.5 technology, 500nits   5.5 inch   19.5 technology, 500nits   5.5 inch   19.80 x 1920   Full HD resolution display, 16:9   Portrait or Landscape, automatic screen rotation   Multi-touch by finger and pen   Eluetooth   Bluetooth 4.2 wireless technology   Class 2   LEE 802.11a/b/g/n/ac compatible   2.4GHz and 5.0GHz, Dual Band support   2.4GHz, Dual Band sup		64GB	
Display Resolution  Resolution  Resolution  Resolution  Resolution  Capacitive  Capacitive  Bluetooth Bluetooth Bluetooth At 2 wireless technology  Vireless  Cellular network Location  Built-in GNSS  Ambient Light sensor, 3-axis Motion sensor  Audio  Mono Speaker  Camera  ZMP front, 5MP rear  Keyboard  Interfaces  Audio Ago and Ago		Intel HD Graphics	
Touchscreen Bluetooth Bluetooth 4.2 wireless technology Class 2 Wireless Cellular network Location Built-in GNSS Sensors Ambient Light sensor, 3-axis Motion sensor Audio Mono Speaker Camera Keyboard Interfaces USB port SIM Card Slot Charging - DC in power Docking connector Built-in Barcode scanner Doublit-in Not Reader Security Power  Expansion Slots * Security Power  Cooling System Dimensions Weight Environment **  Cooling System Dimensions Weight Environment **  Regulatory Ordering Code Regulatory Ordering Code Regulatory Accessories *  Capacitive Built-in Set stance Bluetooth 4.2 wireless technology Capacitive Sind Card Slot Support GPS, Glonass and Assisted GPS Support GPS, Glonass and Assisted GPS AutoFocus rear camera Focus rear camera AutoFocus rear camera Focus rear camera	•	5.5 inch	IPS technology, 500nits
Touchscreen Bluetooth Bluetooth 4.2 wireless technology Class 2 Wireless Cellular network Location Built-in GNSS Sensors Ambient Light sensor, 3-axis Motion sensor Audio Mono Speaker Camera Keyboard Interfaces USB port SIM Card Slot Charging - DC in power Docking connector Built-in Barcode scanner Doublit-in Not Reader Security Power  Expansion Slots * Security Power  Cooling System Dimensions Weight Environment **  Cooling System Dimensions Weight Environment **  Regulatory Ordering Code Regulatory Ordering Code Regulatory Accessories *  Capacitive Built-in Set stance Bluetooth 4.2 wireless technology Capacitive Sind Card Slot Support GPS, Glonass and Assisted GPS Support GPS, Glonass and Assisted GPS AutoFocus rear camera Focus rear camera AutoFocus rear camera Focus rear camera	Resolution	1080 x 1920	Full HD resolution display, 16:9
Touchscreen Bluetooth Bluetooth 4.2 wireless technology Class Clebular network Cellular network Cellular network Cellular network Cellular network Cellular network Cellular network Cemera Built-in GNSS Sensors Ambient Light sensor, 3-axis Motion sensor Audio			
Bluetooth Wireless   Bluetooth 4.2 wireless technology   IEEE 802.11a/b/g/n/ac compatible   2.4GHz and 5.0GHz, Dual Band support	Touchscreen	Capacitive	
Cellular network Location Built-in GNSS Sensors Ambient Light sensor, 3-axis Motion sensor  Audio Camera Keyboard Interfaces  Losa June June June June June June June June	Bluetooth	Bluetooth 4.2 wireless technology	Class 2
Location Sensors Ambient Light sensor, 3-axis Motion sensor Audio Mono Speaker Camera ZMP front, 5MP rear Keyboard Interfaces  USB port SIM Card Stot Charging - DC In power Docking connector Built-in BFC reader Security Power Built-in FC reader  Cooling System Dimensions Weight Environment **  Environ	Wireless	IEEE 802.11a/b/g/n/ac compatible	2.4GHz and 5.0GHz, Dual Band support
Ambient Light sensor, 3-axis Motion sensor Audio Mono Speaker ZMP front, 5MP rear  Keyboard Interfaces USB port SIM Card Slot Charging - DC In power Built-in Barcode scanner Built-in Pro reade Built-in rechargeable lithium-ion battery Dimensions Weight Environment**  Weight Environment**  Regulatory Ordering Code Included in the box Accessories*  Ambient Light sensor, 3-axis Motion sensor Mono Speaker AutoFocus rear camera ID and 2D barcode support Built-in NFC reader  Fand-user replaceable battery AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cendus Segion - 10 °C to 50 °C  Operating Temperature Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cendus Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cendus Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cendus Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cendus Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cendus Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Ceoling System Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Ceoling System Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Ceoling System Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3	Cellular network		
Audio Camera ZMP front, 5MP rear AutoFocus rear camera Keyboard Interfaces USB port SIM Card Slot Charging - DC In power Built-in Barcode scanner Built-in NFC reader Security Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Dimensions Weight Environment Environme	Location	Built-in GNSS	Support GPS, Glonass and Assisted GPS
Audio Camera ZMP front, 5MP rear AutoFocus rear camera Keyboard Interfaces USB port SIM Card Slot Charging - DC In power Built-in Barcode scanner Built-in NFC reader Security Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Dimensions Weight Environment Environme	Sensors	Ambient Light sensor, 3-axis Motion sensor	
New Power button, Volume control, Barcode scanner button (and 4 programmable buttons by software)   USB port	Audio	-	
Interfaces  USB port SIM Card Slot Charging - DC In power Docking connector Built-in Barcode scanner Expansion Slots * Security Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter AC/DC Power Adapter Height 180mm, Width 87mm, Depth 21.5mm Weight Bnyrox.360g Environment **  Poystem High & Low, Shock Temperature Humidity Dust Resistance Drop Resistance Drop Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Val Type-A and Micro USB X1 Type-A and Micro Usp X1 by Jack X1 Dy Jack X1 Dy Jack X1 Dy Jack X1 Dy Jack X2 Dy Jack X2 Dy Jack X3 Dy Jack X2 Dy Jack X3 Dy Jack X4 Dy Jack	Camera	2MP front, 5MP rear	AutoFocus rear camera
SIM Card Slot Charging - DC In power Docking connector Built-in Barcode scanner  Expansion Slots * Security Power  Ac/DC Power Adapter Dimensions Height 180mm, Width 87mm, Depth 21.5mm Baprox.360g Environment **  Environment **  Regulatory Ordering Code Included in the box Accessories *  SIM Card Slot Charging - DC In power At 1by Jack At 1	Keyboard	Power button, Volume control, Barcode scanner button (and 4 programmable buttons by software)	
Charging - DC In power Docking connector Built-in Barcode scanner Expansion Slots * Built-in NFC reader Trusted Platform Module (TPM) 2.0  Built-in rechargeable lithium-ion battery AC/DC Power Adapter Dimensions Height 180mm, Width 87mm, Depth 21.5mm Weight Environment **  No perating Temperature High & Low, Shock Temperature Humidity Dust Resistance Water Resistance For power Regulatory Ordering Code Included in the box Accessories *  Charging - DC In power Alapter All D and 2D barcode support Accessories * All D and 2D barcode support All D and 2D and All Shift All S	Interfaces	USB port	x1 Type-A and Micro USB
Docking connector Built-in Barcode scanner Built-in NFC reader  Security Power Built-in NFC reader Trusted Platform Module (TPM) 2.0 Built-in rechargeable lithium-ion battery AC/DC Power Adapter Fanless design - No fan. No noise. Dimensions Weight Environment ** Poperating Temperature High & Low, Shock Temperature For Resistance For R		SIM Card Slot	x1
Expansion Slots *  Built-in NFC reader  Security  Power  Built-in rechargeable lithium-ion battery  AC/DC Power Adapter  Fanless design - No fan. No noise.  Dimensions  Weight  Environment **  Poyerating Temperature High & Low, Shock Temperature Humidity Dust Resistance Water Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Built-in NFC reader  Built-in NFC reader  Built-in NFC reader  SolomAh, ample power for a full shift End-user replaceable battery  5000mAh, ample power for a full shift End-user replaceable battery  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 6A  F		Charging - DC In power	x1 by Jack
Expansion Slots * Security Power  Built-in NFC reader Trusted Platform Module (TPM) 2.0  Built-in rechargeable lithium-ion battery  AC/DC Power Adapter Fanless design - No fan. No noise.  Poimensions Weight End-user replaceable battery AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise. Height 180mm, Width 87mm, Depth 21.5mm approx.360g  Environment **  Operating Temperature High & Low, Shock Temperature Humidity Dust Resistance Water Resistance Vater Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  New Guild Included In the Box Accessories *  Built-in NFC reader Trusted Platform Module (TPM) 2.0  5000mAh, ample power for a full shift End-user replaceable battery 5000mAh, ample power for a full shift End-user replaceable battery 5000mAh, ample power for a full shift End-user replaceable battery 1000-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless-desible battery 1000-240VAC, 50/60Hz, Output: 5VDC, 50  Cooling Stream-100-240VAC, 50/60Hz, Output: 5VDC, 50  Fanless-desible battery 1000-240VAC, 50/60Hz, Output: 5000-240VAC, 50/60Hz, Output: 5000-240VAC, 50/60Hz, Output: 5000-240VAC, 50/60Hz, Outpu		Docking connector	x1
Security Power  Built-in rechargeable lithium-ion battery  AC/DC Power Adapter  Fanless design - No fan. No noise.  Dimensions  Weight  Environment **  Operating Temperature Humidity Dust Resistance Water Resistance Drop Resistance Drop Resistance Cordering Code Included in the box Accessories *  Trusted Platform Module (TPM) 2.0  Built-in rechargeable lithium-ion battery 5000mAh, ample power for a full shift End-user replaceable battery Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fan. No noise.  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fanle store input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fanle store input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Fanless design - No fanle store input: 100-240VAC, 50/60Hz, Output: 5VDC, 50/		Built-in Barcode scanner	1D and 2D barcode support
Power  Built-in rechargeable lithium-ion battery  AC/DC Power Adapter  Cooling System Dimensions Weight Environment **  Operating Temperature High & Low, Shock Temperature Humidity Dust Resistance Drop Resistance Drop Resistance Coolar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Built-in rechargeable lithium-ion battery  5000mAh, ample power for a full shift End-user replaceable battery  100-240VAC, 50/60Hz, Output: 5VDC, 3A  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 5	Expansion Slots *	Built-in NFC reader	
Cooling System Dimensions Weight AC/DC Power Adapter Panless design - No fan. No noise.  Height 180mm, Width 87mm, Depth 21.5mm  Weight Acyperating Temperature High & Low, Shock Temperature Humidity Dust Resistance Drop Resistance Drop Resistance Accessories *  Pagulatory  Ordering Code Included in the box Accessories *  End-user replaceable battery Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  End until 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 50 °C  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 60 °C  In accordance with MIL-STD-810G  In acc	Security	Trusted Platform Module (TPM) 2.0	
AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Cooling System Fanless design - No fan. No noise.  Height 180mm, Width 87mm, Depth 21.5mm  approx.360g  Operating Temperature High & Low, Shock Temperature Humidity Dust Resistance IP6x Water Resistance IP75 Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Accessories *  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A  Input: 100-240VAC, 50/60Hz, Output: 5VDC, 64  In accordance with MIL-STD-810G  In accordanc	Power	Built-in rechargeable lithium-ion battery	5000mAh, ample power for a full shift
Cooling System Dimensions Height 180mm, Width 87mm, Depth 21.5mm  Weight  Environment **  Operating Temperature Humidity Dust Resistance Drop Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Fanless design - No fan. No noise. Height 180mm, Width 87mm, Depth 21.5mm  approx.360g  Operating Temperature -10 °C to 50 °C High & Low, Shock Temperature in accordance with MIL-STD-810G  Pless IP6x Water Resistance IPx5 Drop Resistance Solar Radiation, Altitude, Vibration and Shock in accordance with MIL-STD-810G  CE, MIL-STD-810G, WEEE, RoHS RP 550, 4GB RAM, 64GB SSD, Barcode, OS Windows Hand holder, Power Adapter, Quick User Guide, Warranty document Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.			End-user replaceable battery
Dimensions Weight Approx.360g  Environment **  Operating Temperature High & Low, Shock Temperature Humidity Dust Resistance Drop Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Height 180mm, Width 87mm, Depth 21.5mm  Approx.360g  Operating Temperature In accordance with MIL-STD-810G In accordance with MIL-STD-810G IP6x IPx5 IPx5 In accordance with MIL-STD-810G In accordance with MIL		AC/DC Power Adapter	Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A
Weight approx.360g  Environment **  Operating Temperature High & Low, Shock Temperature Humidity Dust Resistance Water Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Operating Temperature In accordance with MIL-STD-810G In accordance with MIL-STD-810G In accordance with MIL-STD-810G In accordance with MIL-STD-810G  Fragilatory Ordering Code Included in the box Accessories *  Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Cooling System	Fanless design - No fan. No noise.	
Environment **  Operating Temperature High & Low, Shock Temperature Humidity Dust Resistance Water Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories *  Operating Temperature High & Low, Shock Temperature In accordance with MIL-STD-810G IP6x IPx5 IPx5 IPx5 In accordance with MIL-STD-810G CE, MIL-STD-810G, WEEE, RoHS Ordering Code Included in the box Accessories *  Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Dimensions	Height 180mm, Width 87mm, Depth 21.5mm	
High & Low, Shock Temperature in accordance with MIL-STD-810G Humidity 0% to 90% relative humidity, non-condensing Dust Resistance IP6x Water Resistance IPx5 Drop Resistance 1.22m Solar Radiation, Altitude, Vibration and Shock in accordance with MIL-STD-810G  Regulatory CE, MIL-STD-810G, WEEE, ROHS Ordering Code RP 550, 4GB RAM, 64GB SSD, Barcode, OS Windows Included in the box Accessories * Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Weight	approx.360g	
Humidity Dust Resistance Prop Resistance Drop Resistance Drop Resistance Solar Radiation, Altitude, Vibration and Shock Included in the box Accessories*  Humidity Dust Resistance IP6x IPx5 IPx5 IPx5 IPx5 Included in the box Accessories*  Hand holder, Power Adapter, Quick User Guide, Warranty document Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Environment **	Operating Temperature	-10 °C to 50 °C
Dust Resistance Water Resistance IPx5 Drop Resistance IPx5 Drop Resistance IPx5 Drop Resistance Inaccordance with MIL-STD-810G Regulatory CE, MIL-STD-810G, WEEE, RoHS Ordering Code Included in the box Accessories * Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.		High & Low, Shock Temperature	in accordance with MIL-STD-810G
Water Resistance Drop Resistance Drop Resistance 1.22m Solar Radiation, Altitude, Vibration and Shock in accordance with MIL-STD-810G  Regulatory CE, MIL-STD-810G, WEEE, RoHS Ordering Code Included in the box Accessories * Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.		Humidity	0% to 90% relative humidity, non-condensing
Drop Resistance Solar Radiation, Altitude, Vibration and Shock in accordance with MIL-STD-810G  Regulatory CE, MIL-STD-810G, WEEE, RoHS Ordering Code Included in the box Accessories * Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.		Dust Resistance	IP6x
Solar Radiation, Altitude, Vibration and Shock in accordance with MIL-STD-810G  Regulatory CE, MIL-STD-810G, WEEE, RoHS  Ordering Code RP 550, 4GB RAM, 64GB SSD, Barcode, OS Windows  Included in the box Hand holder, Power Adapter, Quick User Guide, Warranty document  Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen,  Spare Battery, Office Docking with Battery Charger, Carrying Case,  Adapter for cigarette lighter socket, AC/DC Power Adapter.		Water Resistance	IPx5
Regulatory  CE, MIL-STD-810G, WEEE, RoHS  Ordering Code  RP 550, 4GB RAM, 64GB SSD, Barcode, OS Windows  Included in the box Accessories *  Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen,  Spare Battery, Office Docking with Battery Charger, Carrying Case,  Adapter for cigarette lighter socket, AC/DC Power Adapter.		Drop Resistance	1.22m
Ordering Code Included in the box Accessories *  RP 550, 4GB RAM, 64GB SSD, Barcode, OS Windows Hand holder, Power Adapter, Quick User Guide, Warranty document Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.		·	in accordance with MIL-STD-810G
Included in the box Accessories * Hand holder, Power Adapter, Quick User Guide, Warranty document Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Regulatory	CE, MIL-STD-810G, WEEE, RoHS	
Accessories * Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Ordering Code		
Spare Battery, Office Docking with Battery Charger, Carrying Case, Adapter for cigarette lighter socket, AC/DC Power Adapter.	Included in the box		
Adapter for cigarette lighter socket, AC/DC Power Adapter.	Accessories *		
Services * Extended warranty, Battery protection, Accidental damage cover, Fast swanning			
	Services *	Extended warranty, Battery protection, Accidental da	mage cover, Fast swapping.

## www.ruggtek.com

<sup>\*\*\*</sup> Tested by an independent third-party lab following CE, MIL-STD-810G and IEC 60529.
\*\*\* Non-Standard Part, assembly by request. A minimum order quantity (MOQ) is required.