

TABLET 310 GNSS SURVEYING







Rugged Tablet for Measuring and Surveying connecting to Telescopic GNSS receiver Pole.



Android OS
Display 10" Multi-Touch
Sunlight Readable
Big Memory Capacity
Wireless, Bluetooth & Cellular Network
Cradle holder fixing to telescopic pole

www.ruggtek.com



Model	RTA 310 GNSS Surveying	
Operating System	Android 11	support Google play store and services
Computing Platform	MediaTek MT8788	8 Cores, up to 2.00GHz
System Memory	6GB	8GB ***
Storage	128GB	256GB ***
Graphic	ARM Mali-G72	
Display	10.1 inch	High brightness 1000nits, Sunlight readable
Resolution	1920 x 1200	2K resolution display, 16:10
		Portrait or Landscape, automatic screen rotation
Touchscreen	Capacitive	Multi-touch by finger and pen
Ethernet	Fast Ethernet 100Mbit/s	, , ,
Bluetooth	Bluetooth 4.2 wireless technology	Class 2
Wireless	IEEE 802.11a/b/g/n/ac compatible	2.4GHz and 5.0GHz, Dual Band support
Cellular network	4G LTE	Voice and data
Location *	Built-in High Precision GNSS	Multi-Constellation, centimetre precision
Sensors	Ambient Light sensor, 3-axis Motion sensor, Magn	
Audio	Mono Speaker and Headphone	, , , , , , , , , , , , , , , , , , , ,
Camera	5MP front, 13MP rear	Flash and Auto focus rear camera
Keyboard	Power button, Volume control	
Interfaces	USB port	x2 Type-A and Type-C
	RJ45 ethernet port	x1
	DB9 serial RS-232	x1
	SIM Card Slot	x1
	SD Memory Card Slot	x1
	Headphone	x1 Line Out 3.5mm
	Charging - DC In power	x1 by Jack
	Docking connector	x1
Power	Built-in rechargeable lithium-ion battery	12000mAh, ample power for a full shift
	g	End-user replaceable battery
	AC/DC Power Adapter	Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A
Cooling System	Fanless design - No fan. No noise.	pan. 100 _ 101/10, 00/00112, 0aipan 0120, 0/1
Mounting	Cradle holder fixing to telescopic pole; offering tilt and swivel adjustments; removable tablet.	
Dimensions	Width 275mm, Height 178mm, Depth 18mm	
Weight	approx.900g	
Environment **	Operating Temperature	-20 °C to 60 °C
	High & Low, Shock Temperature	in accordance with MIL-STD-810G
	Humidity	0% to 90% relative humidity, non-condensing
	Dust Resistance	IP6x
	Water Resistance	IPx5
	Drop Resistance	1.22m
	Solar Radiation, Altitude, Vibration and Shock	in accordance with MIL-STD-810G
Regulatory	CE, FCC, MIL-STD-810G, WEEE, RoHS	3.2.3.22.00
Ordering Code	RTA 310-GTP, 6GB RAM, 128GB SSD, OS Android	
Included in the box	Cradle and Pole Holder, Rubber-tipped Pen, Carry Handle, Power Adapter,	
The Box	Quick User Guide, Warranty document.	,
Accessories *	Tempered Glass hardness 9H for anti-shock and anti-scratch, Spare Battery.	
Services *		

www.ruggtek.com

^{**} Tested by an independent third-party lab following CE, MIL-STD-810G and IEC 60529.
*** Non-Standard Part, assembly by request. A minimum order quantity (MOQ) is required.