

RUGGED TABLET RTL 412



12"



The popular and modern platforms for embedded solutions
based on the Intel CPU New Generation: Jasper Lake.



Linux Ubuntu
Display 12" Touchscreen
8GB Memory Ram
Wireless & Bluetooth
Cellular Network
Keyboard with Touchpad

www.ruggtek.com

| | | |
|---------------------|--|---|
| Model | RTL 412 | |
| Operating System | Linux Ubuntu 22.04.3 LTS | Debian, Fedora, SUSE *** |
| Computing Platform | Intel N5100 | 4 Cores, 4 Threads, up to 2.80GHz |
| System Memory | 8GB | |
| Storage | 128GB | |
| Graphic | Intel UHD Graphics | Dual Display support |
| Display | 12.2 inch | IPS technology, 650nits |
| Resolution | 1920 x 1200 | 2K resolution display, 16:10 |
| | | Portrait or Landscape orientation by software |
| Touchscreen | Capacitive | Multi-touch by finger and pen |
| Ethernet | Gigabit Ethernet 1000Mbit/s | |
| Bluetooth | Bluetooth 5.0 wireless technology | Class 2 |
| Wireless | IEEE 802.11a/b/g/n/ac compatible | 2.4GHz and 5.0GHz, Dual Band support |
| Cellular network | 4G LTE (or 5G ***) | Data |
| Location | - | |
| Sensors | - | Light sensor by software |
| Audio | Speaker and Headphone | |
| Camera | - | |
| Keyboard | Power button, Volume control | |
| Interfaces | USB port | x4 Type-A and Type-C |
| | RJ45 ethernet port | x1 |
| | DB9 serial RS-232 | x1 |
| | HDMI | x1 |
| | SIM Card Slot | x1 |
| | Headphone | x1 Line Out 3.5mm |
| | Charging - DC In power | x1 by Jack |
| | Docking connector | x1 |
| Power | Built-in rechargeable lithium-ion dual battery | 6300+1000mAh, ample power for a full shift |
| | Power Management Hot Swap | End-user replaceable battery |
| | AC/DC Power Adapter | Input: 100-240VAC, 50/60Hz, Output: 12VDC, 4A |
| Cooling System | Fanless design - No fan. No noise. | |
| Mounting | VESA mount | |
| Dimensions | Width 319mm, Height 216mm, Depth 23.4mm | |
| Weight | approx.1500g | |
| Environment ** | Operating Temperature | -20 °C to 60 °C |
| | High & Low, Shock Temperature | in accordance with MIL-STD-810G |
| | Humidity | 0% to 90% relative humidity, non-condensing |
| | Dust Resistance | IP6x |
| | Water Resistance | IPx5 |
| | Drop Resistance | 1.22m |
| | Solar Radiation, Altitude, Vibration and Shock | in accordance with MIL-STD-810G |
| Regulatory | CE, FCC, MIL-STD-810G, WEEE, RoHS | |
| Ordering Code | RTL 412, 8GB RAM, 128GB SSD, OS Linux | |
| Included in the box | Carry Handle, Hand holder, Power Adapter, Quick User Guide, Warranty document | |
| Accessories * | Tempered Glass hardness 9H for anti-shock and anti-scratch, Rubber-tipped Pen, | |
| | Spare Battery, Shoulder strap, Office Docking with Battery Charger, | |
| | Rugged Cradle holder, Rugged Docking with interfaces, Vehicle Docking with interfaces, | |
| | Adapter for cigarette lighter socket, AC/DC Power Adapter, Removable Keyboard. | |
| Services * | Extended warranty, Battery protection, Accidental damage cover, Fast swapping. | |

www.ruggtek.com

* Optional

** Tested by an independent third-party lab following CE, MIL-STD-810G and IEC 60529.

*** Non-Standard Part, assembly by request. A minimum order quantity (MOQ) is required.

Specifications given herein may be changed at any time without any notice.

Copyright © 2024 Ruggtek, registered trademark. All Rights Reserved.